



# Tsunami™

1000BaseSX Wireless Gigabit Ethernet Bridge



## Cost-Effective Gigabit-Speed Capacity

The Tsunami wireless Gigabit Ethernet bridge is the world's first 1000BaseSX system to provide wireless gigabit point-to-point connectivity while preserving native IP. Tsunami Gigabit meets the ever-growing demand for greater WAN/MAN bandwidth at a significantly lower cost than fiber solutions.

Tsunami Gigabit is an ideal alternative to multiple T1s or fiber-optic cable and can be used to extend or provide redundancy to existing fiber networks.

### Tackle Your Toughest Bandwidth Problems

Tsunami wireless Gigabit Ethernet bridges deliver carrier-class wireless solutions that meet critical connectivity needs for:

- Enterprise IT managers building out their private networks by creating WAN/MAN connectivity for building-to-building and campus-to-campus locations
- Service providers extending fiber networks to create new connections for “last-mile” or remote access requirements
- Internet Service Providers expanding the network backbone to establish new points of presence (POP)

### About the Tsunami Product Family

The Tsunami family of Ethernet bridges provides wireless solutions that meet the growing demand for transparent and reliable high-speed network interconnectivity.

In addition to Tsunami 1000BaseSX, the world's first license-exempt Gigabit Ethernet bridge, the Tsunami product line includes:

**Tsunami 10BaseT**, a cost-effective, high-capacity alternative to multiple wireline T1 connections.

**Tsunami 100BaseT/F**, offering wireless Fast Ethernet connectivity for data communications at full-duplex 100BaseT/F speeds.

## PRODUCT HIGHLIGHTS

### Highest Capacity Available

- Removes network bandwidth bottlenecks
- Native IP is preserved throughout the system with direct connections to Gigabit switches

### Easily Installed and Operational the Next Day

- License-exempt, eliminating delays from regulatory approvals
- Faster to deploy than new fiber
- Eliminates schedule delays due to new fiber right-of-way issues

### Accelerates and Maximizes Return on Investment

- Faster payback compared to trenching new fiber or multi-year lease contracts
- Gigabit Ethernet connectivity at half the cost of an OC-3 connection

### Carrier-Class Reliability

- Meets or exceeds traditional Telco wireline standards
- Eliminates line cuts inherent with wireline networks
- Longer distances and highest reliability due to superior system gain

## KEY FEATURES

- License-exempt in many countries
- 430 Mbps full-duplex data capacity
- Four wayside T1 channels included
- Frequency ranges: 5250-5350 MHz and 5725-5825 MHz (U-NII Band)
- Compliant with key industry standards
- Network management through SNMP or HTTP
- Works with VPN (IEEE 802.1Q) for virtual LAN compatibility
- Built-in loopback, far-end monitoring, and private telephone network orderwire
- 2-year warranty

## Product Specifications

PRODUCT	MODEL NUMBER	FREQUENCY BAND	DATA CAPACITY (FULL DUPLEX)	VOICE CAPACITY	CHANNEL PLANS	THRESHOLD (BER=1X10 <sup>-6</sup> )	OUTPUT POWER (MINIMUM)	SYSTEM GAIN	DISTANCE (MILES/KM)
Tsunami 480	27900-G1	5250-5350 MHz and 5725-5825 MHz	430 Mbps	4 x T1	1 (A)	-73 dBm	+10 dBm +15 dBm	83 dB	< 7/11

### System

<b>Frequency Band (Dual)</b>	5250-5350 MHz and 5725-5825 MHz
<b>Aggregate Capacity</b>	872 Mbps
<b>Data Capacity</b>	430 Mbps Full Duplex
<b>Voice Capacity</b>	4 x T1
<b>Antenna Connector</b>	Two (2) N-Type female
<b>Output Power (5.8 GHz)</b>	+15 dBm
<b>(5.3 GHz)</b>	+10 dBm
<b>RF Attenuation Range</b>	16 dB, minimum
<b>Receiver Threshold</b>	-73 dBm, BER=1x10 <sup>-6</sup> , min.
<b>System Gain</b>	83 dB
<b>Maximum Receive Level</b>	-20 dBm, error-free
<b>Latency</b>	<500 μs
<b>Regulatory Compliance</b>	US: FCC Part 15.407, Class A Canada: IC RSS-210

### Data Interface

<b>Gigabit Ethernet Interface</b>	1000BaseF(SX)
<b>Connector</b>	SC
<b>Compliance</b>	IEEE 802.3d, 802.3z, 802.1q

### Telco Interface

<b>Interface</b>	DSX-1
<b>Connector</b>	RJ-48C female
<b>Compliance</b>	ANSI T1-102-1987

### Auxiliary Connections

<b>Orderwire Handset</b>	2-wire, RJ-11
<b>VF Orderwire Bridge</b>	600 ohm, balanced, 4-wire, 0 dBm, DB9
<b>Configuration Port</b>	RS-232, DB9 Software download
<b>Network Management (NMS)</b>	10/100BaseT/F (HTTP, SNMP)
<b>Aux. Data Port (Clear Service Channel)</b>	RS-232/RS-422, 19.2k baud, DB9
<b>Alarm Port</b>	2 ea. Form C, 6 ea. TTL, DB9
<b>Test Points</b>	Output power, near- and far-end RSL
<b>Wayside Channels</b>	4 x T1 (DSX-1)

### Power/Environment

<b>DC Power</b>	±37 to ±63 Volts, <250 Watts
<b>Optional AC Adapter</b>	100-250 Volts, 50-60 Hz
<b>Power Connector</b>	6-pin barrier strip, plug-in
<b>Operational Temperature</b>	
<b>Indoor Unit</b>	0° to +50° C
<b>Outdoor Unit</b>	-30° to +65° C
<b>Humidity</b>	0 to 95% non-condensing
<b>Altitude</b>	15,000 feet/4572 meters, maximum

### Physical

<b>Indoor Unit</b>	
<b>Size (WxHxD)</b>	17.2 x 3.5 x 14.5 inches (2RU) 43.7 x 8.9 x 36.8 cm
<b>Weight</b>	11 lbs/5 kg
<b>Outdoor Unit</b>	
<b>Size (WxHxD)</b>	9 x 13 x 5 inches 22.9 x 33 x 12.7 cm
<b>Weight</b>	20 lbs/9 kg

### Mounting (Installation)

<b>EIA Rack Mount</b>	19-inch/48.2 cm, 2-rack unit height (mounting brackets supplied)
-----------------------	--



**Proxim Corporation** tel: 800.229.1630  
935 Stewart Drive tel: 408.731.2700  
Sunnyvale, California 94085 fax: 408.731.3675